TECHNICAL INFORMATION SHEET

Single Ply LVOC Splice Wash

TIS # 826

ITEM NUMBER: W563587113

Description:

Firestone Seam Cleaner LVOC is designed to clean and prepare dirty RubberGard™ EPDM and UltraPly™ TPO membranes to be welded, or receive Firestone Primers, Adhesives and Sealants. Membrane cleaned with Seam Cleaner LVOC to receive QuickSeam™ tape products shall be further prepared by the application of the appropriate Firestone Primer.

Method of Application:

1. Surfaces to be welded, or receive Firestone Primers, Adhesives and Sealants shall be clean, dry, and free of foreign materials and excess dusting agent. Remove loose contaminates using brooms or rags.
2. Clean/prepare dirty surfaces using clean cotton rags wetted with Seam Cleaner LVOC, in circular motions with heavy pressure over the affected areas. Membrane with caked dirt, including in-service TPO membrane, should be scrubbed using QuickScrubber™ Handle & Pad wetted with Seam Cleaner LVOC, followed by cleaning with clean dry rags to remove contaminates.
3. Allow surfaces cleaned with Seam Cleaner LVOC to dry completely (usually within 10 to 30 minutes) before welding, or applying Primers, Adhesives and Sealants per Firestone's current specifications and details.

Storage:

- Store in original unopened pails indoors at temperatures between 60 °F - 80 °F (16 °C - 27 °C) away from all sources of direct heat and ignition - this is a flammable liquid.
- When exposed to lower temperatures, restore to room temperature prior to use.
- Keep the material out of direct sunlight until ready for immediate use.
- Although there is no shelf life for Splice Wash, it's best to use within one year.

Precautions:

- Flammable liquid. Store and use away form all sources of direct heat and ignition.
- Cover tightly when not in use.
- Thinning is not allowed.
- Use of solvent-resistant Neoprene gloves is required when applying Splice Wash. Do not allow Splice Wash to come in direct contact with skin.
- Avoid breathing vapors.
- Do not use as a pre-wash for any QuickSeam™ Tape products. Single-Ply QuickPrime™, QuickPrime Plus or QuickPrime Plus LVOC must be used for QuickSeam Tape products.
- Refer to Material Safety Data Sheet for further information.

Compliance:

Post Consumer Recycled Content:	0%
Pre Consumer Recycled Content:	0%
Manufacturing Location:	South Bend, IN

Packaging:	
Pails:	3 Gallon Pails
Weight:	≈20 lbs per pail
Coverage Rate:	250-300 ft²/gallon (4.9 - 6.1 m²/L) on one side

Physical Properties:	*Minimum Performance*
Solvents:	Solvent Blend of Acetone & Mineral Spirits
Viscosity:	Very thin, free flowing
Weight:	6.593 ± 0.329 lbs/gal
V.O.C. Content:	Less than 250 g/L

Please Contact your Firestone Roof Systems Advisor at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.