## Firestone Building Products Company, LLC Material Safety Data Sheet

January 4, 2012 Page: 1

SECTION 1: PRODUCT IDENTIFICATION

Product Name: EcoWhite™ EPDM 12" QuickSeam™ Flashing

Chemical Name / Synonym: None
Chemical Family: Mixture

24-Hour Emergency Phone: (800) 424-9300 CHEMTREC

Manufacturer's Name: Firestone Building Products Company, LLC Manufacturer's Address: 250 West 96<sup>th</sup> Street, Indianapolis, IN 46260

NFPA Hazard Rating: Health 1, Flammability 1, Reactivity 0
HMIS Hazard Rating: Health 0, Flammability 1, Reactivity 0

SECTION 2: CHEMICAL COMPOSITION

Common

Chemical Name: Name: CAS #: % (by wt) Exposure Limits: onhazardous as per 29 None None 100 None Established

Nonhazardous as per 29 CFR 1910.1200 None None 100 None Established

SECTION 3: HAZARD IDENTIFICATION

Primary Route of Exposure: Eye contact

Signs and Symptoms of Contact with

Exposure:

Contact with eye may result in mechanical irritation, redness,

tearing and blurred vision.

Medical Conditions Aggravated

by Exposure:

None known.

Chronic Effects: No known adverse effects.

Carcinogenicity: None.

SECTION 4: FIRST AID MEASURES

First Aid Procedures: Treat as a foreign object in eye. Flush large amounts of water,

frequently flushing under the lids. Get medical attention if

irritation persists.

SECTION 5: FIRE FIGHTING PROCEDURES

Suitable Extinguishing Media: Foam, water, dry chemical, or carbon dioxide.

Hazardous Combustion Products: Carbon dioxide and carbon monoxide, oxides of nitrogen, sulfur

dioxide, partially burned carbon.

Recommended Fire Fighting

Procedures:

Treat as a Class "B" fire. Limit fire fighting to those trained to do

so. Minimize breathing gases, vapor, fumes, or decomposition products. Use supplied breathing air equipment for enclosed or

confined spaces or as otherwise needed.

Unusual Fire and Explosion

Hazards:

None known.

SECTION 6: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to Be Taken in Case

se Shovel or scoop into a sealable container for disposal.

Material is Released or Spilled:

## Firestone Building Products Company, LLC Material Safety Data Sheet

January 4, 2012 Page: 2

Precautions to Be Taken in Handling and Storing:

Do not store or handle at temperatures in excess of 130°F. Store in a cool, dry area. Avoid prolonged or repeated contact with the skin. Product readily removed from the skin with waterless hand cleaners followed by washing with soap and water.

SECTION 7: EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: No special ventilation requirements.

Respiratory Protection: None required

Eye Protection: Safety glasses with side shields may be necessary when

handling, cutting or applying this product.

Skin Protection: None required.
Other: None required.

Work / Hygienic Practices: Wash exposed skin prior to eating, drinking or smoking and at

the end of each work shift. Wash contaminated clothing prior to

reuse.

SECTION 8: PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor: White solid with white tacky laminate; rubber odor.

Flash Point: >200° F Lower Explosive Limit: None

Method Used: Estimate based on the Upper Explosive Limit: flash point of the most

volatile component.

Evaporation Rate: Not Applicable Boiling Point: None

pH (undiluted product): Not Applicable Melting Point: Unknown Solubility in Water: None Specific Gravity: Unknown

(Water=1)

None

Unknown

Vapor Density: Not Applicable Percent Volatile:

Vapor Pressure: Not Applicable

SECTION 9: STABILITY AND REACTIVITY

Thermal Stability: Stable

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Exposure to temperature in excess of 130°F.

SECTION 10: TRANSPORTATION

Regulatory Agency:
Proper Shipping Name:
Not Applicable
Hazard Classification:
Not Applicable
Identification Number:
Not Applicable
Labels Required:
Not Applicable
Other Requirements:
Not Applicable

## Firestone Building Products Company, LLC Material Safety Data Sheet

January 4, 2012 Page: 3

SECTION 11: MISCELLANEOUS INFORMATION

Additional Comments: This product is considered to be a finished article as per 29 CFR

1910.1200(C) and is therefore exempt from the requirements of

the Hazard Communication standard.

Date of Previous MSDS: February 9, 2009

Changes Since Previous MSDS: Review only.

Telephone Number for Additional

Information:

(317) 575-7190

## DISCLAIMER

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. Firestone Building Products Company, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Firestone Building Products Company assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.